

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 1 057 751 A1

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
06.12.2000 Bulletin 2000/49

(51) Int Cl.7: B65D 85/04, B65D 81/20,
B65D 19/20, B65D 77/04,
B65D 5/50

(21) Application number: 99830333.3

(22) Date of filing: 31.05.1999

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: Cipriani, Giancarlo
I-52012 BIBBIENA STAZIONE (AREZZO) (IT)

(74) Representative: Gotra, Stefano
BUGNION S.p.A.
No. 25, Via Emilia Est
41100 Modena (IT)

(71) Applicant: C.I.F.E. S.p.A.
52010 Chiusi della Verna (Arezzo) (IT)

(54) Cardboard box for containing and dispensing wire

(57) The cardboard box for containing and dispensing large quantities of wire, especially metal wire for welding, comprises a cubic external container (1) with an open top side, an octagonal-base internal container (2), fitting snugly into the external container (1) and be-

ing destined to contain a coil of wire (3), and a bag-type wrapper (4) made of a flexible airtight material, which is interposed between the external and the internal containers so as completely to cover the internal container (2) and able to be closed and sealed there-upon.




Fig.1

EP 1 057 751 A1

Description

[0001] Special reference is made to boxes destined to contain coils of large quantities of metal wire, in particular welding wire, with weights going from about 50 kg up to 400 kg.

[0002] The use of such large coils means that automatic welding machines, which are fed with the wire, can operate for continuous and extensive time periods.

[0003] The functions, feeding-in and unwinding modes, as well as the type of stresses the boxes are subject to, all lead to very considerable specialisation in their design, i.e. very different to the design specifications required for other types of containers or packaging.

[0004] First of all, the continuous wire is deposited inside the container in such a way that it can be dispensed therefrom without risk of tangling; special geometrical arrangements are already known for introducing the wire (not of direct interest to the present invention, which uses known techniques), as are central reels which prevent the wire from moving about during transport. The wire is introduced into the box by special machines having platforms on which the empty boxes are placed and from which, once filled, they are removed with the help of special machines (due to their weight). The box must therefore be of an easily manoeuvrable type, whether empty or full.

[0005] The box must also be sufficiently sturdy to withstand lateral stresses, which might otherwise cause unacceptable deformations in the shape of the box itself and the coil of wire contained therein, as well as axial stresses, so that several boxes can be piled one on top of another without crushing any one box. These stresses may be of quite large entity, especially if one considers the amount of movement the boxes are subject to at the various phases, such as when they are at the wire producer's plant, when they are being loaded or unloaded (into a lorry, train or even a ship), as well as when they are being delivered to the eventual user.

[0006] The box must also be conformed so that it does not in any way negatively influence the unwinding of the wire.

[0007] Before it is filled, the box has to be as easy as possible to move and store. Once the wire has been used up, the box is not generally regenerated for further use, so it should also be economical and easy to dispose of.

[0008] A first known type of box of the above type is cylindrical (in effect a piece of tubing) which is provided with ends, top and bottom, generally having metal ribs to reinforce the box itself. Sometimes these boxes are provided with handles, either made of metal or other materials. These boxes are made of a specially tough material, which, however, is expensive. Further disadvantages of these boxes are that they have to be disposed of selectively, and are just as big when empty as when full.

[0009] Generally cubic boxes have been devised

which are made up from folded card. These are economical, and can be easily and efficiently destroyed by the user, but are also only limitedly resistant and are therefore not favoured by producers as they cause problems during movement, nor are they preferred by users who often receive them in a deformed state, which renders the wire difficult to use. There exists a further problem, connected with the possible corrosion of the wire which usually happens during sea transport which at times can last for weeks or even months; none of the existing boxes obviates this problem.

[0010] The present invention provides a box which obviates all of the problems and drawbacks described above.

[0011] A further aim of the present invention is to provide a box whose size can be reduced when empty, which is nonetheless easy and fast to assemble and which, after use, can be easily and unproblematically disposed of.

[0012] An advantage of the invention is that it provides a box preventing corrosion of the wire contained in it, even where it is stored in potentially corrosive surroundings, such as in a ship's hold.

[0013] A further advantage of the invention is that it can be stored serially and stably, in considerable numbers.

[0014] These aims and advantages and others besides will all be attained by the present invention as it is characterised in the claims that follow.

[0015] Further characteristics and advantages of the invention will better emerge from the detailed description that follows, of some preferred but non-exclusive embodiments, illustrated purely by way of non-limiting example in the accompanying figures of the drawings, in which:

figure 1 is a perspective view, with some parts removed better to evidence others, of the box of the invention, in a non-closed configuration;

figure 2 is a vertical elevation of the box in the sealed configuration;

figure 3 is a view from above of the box, with some parts removed better to evidence others.

[0016] The box of the invention comprises an external container 1, cube-shaped, having a square bottom base and open at the top - in effect a normal cubic box with lateral flaps 1a which when closed constitute either the top or the bottom base. As is usual in these containers, the flaps 1a can be superposed one on another so as to obtain double-layer top and bottom bases. The container 1 is obtained by folding a sheet of pre-scored cardboard, with a connection at an edge, achieved by use of metal staples, for example, to obtain a lateral side of the container, and by folding the various lateral flaps and connecting them up, for example using adhesive tape, obtaining the bottom base and, when the container is to be closed, also the top base.

[0017] The box comprises a base pallet 6 to which the bottom of the box is anchored and which is the same size as the bottom base of the box. Metal staples could be used to anchor the box flaps to the pallet 6.

[0018] The pallet 6 is usually made of wood and comprises two parallel lower crossbeams 6a arranged slightly recessed from the base outline of the pallet 6 itself.

[0019] The box further comprises an internal container 2 which is octagonal and which fits snugly into the outer box 1; the internal container 2 is also of about the same height as the outer box 1, and is superiorly open (there is in effect no top base on the internal container 2). The internal container 2 is destined to container the coils of wire 3. The lateral sides of the internal container 2 are obtained by folding a pre-scored sheet of cardboard.

[0020] In a possible configuration of the box, the bottom base 2a of the internal container 2 is a flat octagonal element which is inserted snugly into the internal container 2 itself. An inner core 2b is coaxially inserted on the bottom base 2a; this inner core 2b is superiorly open and is obtained by folding a scored cardboard sheet having also tabs at one end which will fit into slits made in the base 2a. The inner core 2b, which is shorter than both containers so as not to obstruct the wire 3 movement, can advantageously be provided with longitudinal inspection slits 2c for visual inspection of the state of the wire coil in the box. A hook 7 can also be coaxially connected to the base 2a, to which, by means of an elastic band 9, a transversal fixture element 10 can be connected, constituted by a wooden rod or preferably a shaped piece of cardboard. The upper edge of the inner core 2b is usually provided with a smooth washer to facilitate wire movement.

[0021] Alternatively to the hook 7, with advantages both for the simplicity of construction and for disposal and destruction of the used box, beneath the base 2a, which may or may not be provided with the inner core 2b and which has a central hole, a stop is provided, for example a flat or elongate element which in any case does not pass through the hole, on which the elastic band 9 coming out of the central hole is threaded. The elastic band, as in the previous case and with the same functions, is connected to the fixture element 10. The bottom base of the internal container can also be left out, with the internal container consequently being made up only of the lateral surface; in this case the hook 7 can be connected directly to the base pallet 6.

[0022] As the above embodiments are obvious, they are not illustrated in the figures of the drawings.

[0023] In the spaces created at the edges of the external container, between the internal container and the external container, four triangular corner-pieces 5 made of folded cardboard are inserted. The corner-pieces 5 are of about the same height as the external container and are inserted during assembly of the container between the external and the internal containers.

[0024] Finally, a bag-type wrapping 4, made of flexible airtight material is interposed between the external and internal containers so as to envelop the internal container. The open end of the wrapping 4 faces and exits from the top base of the external container and is sealed once the coil has been introduced into the box.

[0025] For the wire unwinding/dispensing phase, a transparent plastic cover 8 is used. The cover 8 has a square-section base 8a, open downwards and of the right size to fit snugly on the box; it has a truncoconical upper zone 8b which affords a hole 8c at its top for the wire to come out of and a lateral opening 8d which gives access to the inside of the cover 8. The cover 8 is given to the user and can be re-used several times.

[0026] The box described is very simple and economical to make inasmuch as the constituent parts are all made of cheap materials (normal packaging cardboard, plastic or packaging papers, and low-grade wood for the pallet), and can be transported in flat packs and assembled directly at the wire producer's plant. First of all, the external container 1 is assembled and stapled before being stapled as a whole on to the pallet 6; the lateral surface of the internal container 2 is assembled and inserted into the wrapping 4, both then being introduced into the external container 1. Differently to the external container, the cardboard of the internal container might be advantageously covered at the join zone with adhesive paper so as to avoid superposing one cardboard edge over another for stapling, which might otherwise cause some difficulty when inserting the internal container into the external container.

[0027] Where the internal container is accompanied by an inner core and a base, first the inner core is assembled before being connected to the octagonal base. The hook 7, or stop to which the elastic band 9 exiting from the base 2a is already connected, is attached to the octagonal base. The assembly is then simply inserted into the internal container 2.

[0028] Where an internal container with no base is used, the hook 7, which in this case will be self-tapping, is simply connected up to the pallet 6.

[0029] The four triangular corner-pieces 5 are formed by folding the special cardboard blanks and inserted into the corner spaces.

[0030] As can be seen, the box can be fully assembled at the wire-producer's plant, the whole operation being rapid and simple.

[0031] The box is then arranged on a machine which inserts the wire coil. During this operation the upper lateral flaps of the external container are folded external-wise (see the figure) so as not to obstruct the introduction of the wire; the wrapper 4 can advantageously be folded down over the flaps so as keep them folded back.

[0032] Once the wire has been introduced, a brake element 12 is placed on the coil (the brake element 12 is schematically illustrated in the figures and is of known type). The brake element 12 has the function of favouring a correct unwinding of the wire. The fixture element

10 is then placed on the coil and anchored, by means of the elastic band 9, to the hook 7 or stop, which fix it with a downwards pull. As the inner core has the single function of preventing movements of the coil, the core itself, as has been mentioned, may even be left out. If this is the case, the transversal fixture element 10 might be provided with a cylindrical protuberance which could be inserted to a predetermined depth internally of the coil and removed together with the transversal fixture element, with considerable advantages when the coil is unwound.

[0033] When the coil has been introduced, the wrapper 4 is folded over the internal container and closed by heat-welding, gluing or any other like method, after the air inside the wrapper has been removed by aspiration. The wire is now in a vacuum pack with obvious anticorrosion advantages. The lateral flaps are subsequently closed, using for example adhesive paper. The box is now ready for despatch.

[0034] Once it has arrived at its destination, the box is opened and the fixture element removed. The cover 8 is fixed on the box to facilitate wire unwinding. When empty, the box is easy to dispose of. The wrapper 4 constitutes one of the particularities of the box, as thanks to its position between the internal and external containers it is not susceptible to tearing during transport, nor does it obstruct the operations of introduction and unwinding of the wire. What is more, it protects the internal container, and especially the coil of wire contained therein, from atmospheric agents, especially during sea transport.

[0035] Another particularity of the box is the special conformation of the pallet 6 which, thanks to the slightly recessed position of the crossbeams 6a with respect to the base of the pallet itself, creating easily accessible gripping points, means that the whole box can be moved not only by means of the usual forklift trucks but also by bridge cranes equipped with normal slings whose hoist cables can be safely and easily located in the recesses created by the crossbeams 6a. Other types of box assemblies could also be used with the same pallet conformation.



[0036] Finally, the box, thanks to its "double container" conformation, exhibits considerable sturdiness, strength and protection for the coils of wire. Furthermore, thanks to the presence of the triangular corner-pieces 5, considerable resistance to compression is achieved. All of the foregoing is obtained using materials which are commonly considered to be of modest quality, and which are therefore extremely economical and easily recyclable.

Claims

1. A cardboard box for containing and dispensing large quantities of wire, characterised in that it comprises: a cubic square-base external container (1)

which can be opened at a top side thereof; an octagonal-base internal container (2) of such dimensions as to be fully contained within the square-base area of the external container (1), having about a same height as the external container (1) and being destined to contain a coil of wire (3).

2. The box of claim 1, characterised in that it comprises a bag-type wrapper (4) made of a flexible air-tight material so that a vacuum can be created therein when closed, which wrapper (4) is interposed between the external container (1) and the internal container (2) so that the internal container (2) is contained within the wrapper (4); an open end of the wrapper (4) projects superiorly of the external container (1).
3. The box of claim 1, characterised in that it comprises four triangular corner-pieces (5) made of folded cardboard, which have about a same height as the external container (1) and which are inserted between the internal container (2) and the external container (1) in empty spaces created at corners of the external container (1) when the internal container (2) is fitted into the external container (1).
4. The box of claim 1, characterised in that it comprises a base pallet (6) to which a bottom base of the external container is solidly anchored, which pallet (6) comprises two supporting crossbeams (6a) arranged parallel one to another, the crossbeams (6a) being slightly recessed from two parallel edges of the pallet (6).
5. The box of claim 1, characterised in that a bottom base (2a) of the internal container (2) is a flat octagonal element which inserts snugly into the internal container (2); an inner core being coaxially connected on said bottom base (2a), said inner core being superiorly open and being obtained by means of a folding of a cardboard form; a hook (7) being coaxially connected on said bottom base (2a).
6. The box of claim 1, characterised in that the bottom base (2a) of the internal container (2) is a flat octagonal element which inserts snugly into the internal container (2); said bottom base (2a) affording a central hole; a stop being provided below said bottom base (2a) on which stop an elastic band (9) is threaded, which elastic band (9) exits superiorly from said central hole.
7. The box of claim 1, characterised in that the internal container has neither a top nor a bottom base.
8. The box of claim 1, characterised in that it comprises a cover (8) made of transparent plastic which is provided with a square-section base (8a) which is





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 83 0333

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 4 160 533 A (KOTZUR ET AL.) 10 July 1979 (1979-07-10) * the whole document *	1	B65D85/04 B65D81/20 B65D19/20 B65D77/04 B65D5/50
Y	---	2,4,10	
X	US 5 735 429 A (WHITWORTH) 7 April 1998 (1998-04-07) * the whole document *	1	
Y	---	3	
Y	FR 2 747 995 A (LINDAL FRANCE) 31 October 1997 (1997-10-31) * the whole document *	2	
Y	US 4 724 960 A (GOODRUM ET AL.) 16 February 1988 (1988-02-16) * column 3, line 2 - line 9; figures *	3	
A	WO 98 52844 A (ESAB) 26 November 1998 (1998-11-26) * the whole document *	1,6,7	
A	US 5 819 934 A (COOPER) 13 October 1998 (1998-10-13) * abstract; figures *	1,5,7	TECHNICAL FIELDS SEARCHED (Int.Cl.7) B65D
A	WO 94 19258 A (SIDERGAS) 1 September 1994 (1994-09-01) * abstract; figures * * page 6, line 8 - line 16 *	1,8	
Y	GB 2 092 110 A (BALDWIN PACKAGING) 11 August 1982 (1982-08-11) * the whole document *	4,10	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 16 May 2000	Examiner Gino, C
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03.02 (P6/C01)



European Patent
Office

Application Number

EP 99 83 0333

CLAIMS INCURRING FEES

The present European patent application comprised at the time of filing more than ten claims.

- ☐ Only part of the claims have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims and for those claims for which claims fees have been paid, namely claim(s):
- ☐ No claims fees have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims.

LACK OF UNITY OF INVENTION

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

see sheet B

- ☒ All further search fees have been paid within the fixed time limit. The present European search report has been drawn up for all claims.
- ☐ As all searchable claims could be searched without effort justifying an additional fee, the Search Division did not invite payment of any additional fee.
- ☐ Only part of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the inventions in respect of which search fees have been paid, namely claims:
- ☐ None of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the invention first mentioned in the claims, namely claims:



European Patent
Office

LACK OF UNITY OF INVENTION
SHEET B

Application Number
EP 99 83 0333

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

1. Claim : 1 2 9

A cardboard box for containing and dispensing large quantities of wire, comprising an external container, an internal container and a bag interposed between them.

2. Claims: 3 5-8

A cardboard box for containing and dispensing large quantities of wire, comprising an external container, an internal container, triangular corner-pieces, an inner core, a hook connected on the bottom base of the internal container, an elastic band and a transparent plastic cover.

3. Claim : 4 10

A box solidly anchored on a base pallet, which pallet comprises two supporting crossbeams slightly recessed from two parallel edges of the pallet.

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 83 0333

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

16-05-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4160533 A	10-07-1979	CA 1129381 A	10-08-1982
US 5735429 A	07-04-1998	NONE	
FR 2747995 A	31-10-1997	NONE	
US 4724960 A	16-02-1988	NONE	
WO 9852844 A	26-11-1998	AU 3365097 A	11-12-1998
US 5819934 A	13-10-1998	NONE	
WO 9419258 A	01-09-1994	IT VR930008 U	23-08-1994
		AT 159911 T	15-11-1997
		DE 69406605 D	11-12-1997
		DE 69406605 T	05-03-1998
		EP 0636098 A	01-02-1995
		ES 2109680 T	16-01-1998
		US 5494160 A	27-02-1996
GB 2092110 A	11-08-1982	NONE	

CPO FORM 19459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 83 0333

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

16-05-2000

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 4160533	A	10-07-1979	CA	1129381 A	10-08-1982
US 5735429	A	07-04-1998	NONE		
FR 2747995	A	31-10-1997	NONE		
US 4724960	A	16-02-1988	NONE		
WO 9852844	A	26-11-1998	AU	3365097 A	11-12-1998
US 5819934	A	13-10-1998	NONE		
WO 9419258	A	01-09-1994	IT	VR930008 U	23-08-1994
			AT	159911 T	15-11-1997
			DE	69406605 D	11-12-1997
			DE	69406605 T	05-03-1998
			EP	0636098 A	01-02-1995
			ES	2109680 T	16-01-1998
			US	5494160 A	27-02-1996
GB 2092110	A	11-08-1982	NONE		

EPO FORM P0159

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82